

DALO[®] Marker

Industrial Steel Ball Tip Paint Marker

DIRECTIONS

- To start flow press rubber bulb to pressurize
- Depress ball tip to start flow
- Wipe tip clean before storing

FEATURES

- Heavy duty, industrial paint marker that writes on almost any surface
- Writes through oil and grease without losing legibility or brightness.
- Makes permanent bright marks on metal, rubber, plastic, glass, concrete, leather, stone, wood, vinyl and more.
- Marks in extreme weather and temperature conditions, even writes under water and on rusty surfaces.
- Ergonomically correct marker that enables you to mark at all angles, even upside down.
- Markers can be used to permanently identify inventory, assemblies, tools, work in progress or finished products while resisting most work related abuses or compounds.
- Heavy duty aluminum body with large paint capacity.
- Paint flow is controlled by the pressure bulb at the end of the barrel.
- Stainless steel ball tips won't wear out on rough or rusty surfaces.

MATERIALS COMPATIBILITY

- •
- Safe on most surfaces.
- Removable with DYKEM® Remover & Cleaner.
- Surface tests should be run to determine compatibility prior to use.

HEALTH AND SAFETY

- Combustible liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.
- Refer to SDS (Safety Data Sheet) for complete information on health and safety. Visit our website at www.dykem.com to obtain an MSDS.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid		
Odor	Aromatic		
Flash Point	108°F		
Boiling Point / Range	318 - 338°F (158.89 - 170°C)		
Evaporation Rate	<1 (BuAc = 1)		
Specific Gravity	>1		
Water Solubility	Slightly soluble		
VOC Content	28.97 - 35.58%		
Dry Time	25-30 minutes *Note: Drying time may vary depending on film		

AVAILABLE IN

Units/Case	Color	Marker Tip	Part #
48	black	medium, steel	26033
48	blue	medium, steel	26013
48	green	medium, steel	26043
48	red	medium, steel	26023
48	white	medium, steel	26083
48	yellow	medium, steel	26063

