

ROYCO[®] 11MS

HIGH LOAD GENERAL PURPOSE AIRCRAFT GREASE

DESCRIPTION

ROYCO 11MS is a smooth, gray-black colored grease which utilizes an inorganic gel thickener for high temperature operation. A modern additive package is provided containing molybdenum disulfide for high load carrying ability as well as corrosion and oxidation protection, rust inhibitors, and severe duty performance over extreme temperature ranges.

APPLICATIONS

ROYCO 11MS is intended for use in high load, sliding surface applications where severe operating conditions may include temperatures from -40 to 300°F or corrosive environments. Its exceptional water resistance and load carrying properties make it suitable for use in bogie pivot pins and other landing gear assemblies, actuators, and other airframe applications requiring high load carrying performance and resistance to water and corrosives. **ROYCO 11MS** is useful in many industrial applications as well, which require a wide latitude, severe duty general-purpose grease.

APPROVALS and SPECIFICATIONS

ROYCO 11MS is specified for use in landing gear assemblies of many Boeing, McDonnell Douglas, and other transport aircraft.

TYPICAL PROPERTIES:

PROPERTY	Method	ROYCO [®] 11MS
Penetration, Worked, 77°F, 0.1 mm	ASTM D217	332
Color compared to standard		Pass
Workmanship		Pass
Odor		Pass

LIMITATIONS

ROYCO 11MS should not be used in high speed bearing applications without prior performance evaluation.

PACKAGING

35 pound pails. Other package sizes may be available on special request.

Anderol Specialty Lubricants
A division of Chemtura Corporation
215 Merry Lane
East Hanover, NJ 07936 USA

Technical Service +1.973.887.7410
Customer Service +1.203.573.4595
Fax 203.573.2324
info-anderol@chemtura.com
www.anderol.com

The information contained herein relates to a specific Chemtura product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet constitutes a term or condition of sale nor shall it take precedence over, supersede or modify or be construed to take precedence over, supersede or modify, any of Chemtura's standard or other terms and conditions of sale under which the product is sold by Chemtura. NOTHING IN THIS TECHNICAL DATA SHEET CONSTITUTES, NOR SHALL IT BE CONSTRUED TO CONSTITUTE, A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner. This product is sold only under terms and conditions agreed in writing by Chemtura and the respective buyer and the terms and conditions of such agreements shall in all cases prevail. ANDEROL, ROYCO, AOSyn and PQ and their corresponding logos are trademarks of Chemtura Corporation or one of its subsidiaries. Copyright (c) 2010 Chemtura Corporation. All rights reserved.



Anderol Specialty Lubricants
a division of Chemtura Corporation
215 Merry Lane
East Hanover, New Jersey 07936
Technical Service +1.973.887.7410
Customer Service +1.203.573.4595
Fax +1.203.573.2324
info-anderol@chemtura.com
www.anderol.com