
# **POLYKEN®**



## **Premium Grade Duct Tape**



Backing: PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Silver, Olive Drab, Black

Specifications: N/A

Standard Sizes: 48mm x 55M, 72mm x 55M

#### **Applications**

- Waterproof covering for pipe and thermal insulation
- Media-blast protection

- Challenging repair, bundling, and seaming applications
- Waterproof packaging

#### Features

	Deni	JIII3
liah tancila	stronath for	difficult an

•	PE-Coated	Cloth	Backing

High tensile strength for difficult applications

Ranafite

- Tough and durable
- Extremely conformable
- Crisp, straight tear
- Natural Rubber Based Adhesive
- Exceptional performance in cold weather
- Moisture, solvent, and abrasion resistant
- Aggressive adhesion to all surfaces
- Extremely high tack

### **Typical Test Values**

	Standard UOM	Metric UOM	Test Method
Total Thickness	12.0 mils	0.305 mm	ASTM D-1000
Adhesion to Steel	90 oz/in	9.85 N/cm	PSTC-101
Adhesion to Backing	48 oz/in	5.25 N/cm	PSTC-101
Tensile Strength	36 lb/in	63.05 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

