Technical Data

Supplied by: Sil-Mid Limited Roman Park, Roman Way Coleshill, West Midlands B46 1HG. UK T: 01675 432850 E: info@silmid.com

Emergency Telephone No. +44 (0)1675 432850 (Monday to Friday, 08:00 – 17:30 – GMT)



Performance you can trust



BELT DRESSING Spray



Conditioning spray for most types of belt drives

Product Overview

ROCOL[®] BELT DRESSING Spray is a colourless, non-toxic, adhesive spray that reduces slippage and conditions belts extending their service life even in damp or wet conditions.

One application of ROCOL BELT DRESSING Spray will give instant grip to prevent belt squeal, wear and slippage.

Features and Benefits

- ROCOL BELT DRESSING Spray has metal detectable plastic components (aerosol caps and actuators) capable of detection by most metal detection equipment.
- Excellent temperature resistance -50°C to +100°C.
- BELT DRESSING Spray extends belt life and transmission efficiency by conditioning belts to prevent drying out, cracking and ultimately breakage.
- Thin adhesive film increases adhesion when the belts are in contact with drive pulleys, reducing belt slippage which causes glazing, overheating and drying out.
- BELT DRESSING Spray is equally effective in damp or wet environments as in dry and clean conditions due to its insolubility in water.
- Blue spray nozzle for easy identification as a foodsafe product.

Directions for Storage and Use

- Shake aerosol well before use.
- Apply from a distance of 15-30 cm (6-12 inches).
- For best results apply a thin film directly onto the drive face of the belt.
- Ensure adequate ventilation during use.
- Test compatibility with plastics and rubbers and painted or coated surfaces prior to application
- The storage temperature should be kept below +50°C, and the storage area should be out of direct sunlight.
- Shelf life is 5 years from date of manufacture.

Specifications

- BELT DRESSING Spray does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- BELT DRESSING Spray is manufactured from only FDA listed ingredients:
- FDA Group 21 CFR 178.3570
- BELT DRESSING Spray is NSF registered:
- NSF H1 registered 123700
- ISO 21469 certified

Pack Sizes

Pack Size	Part Code
300ml	34295

ROCOL A division of IT W Ltd





ROCOL House, Swillington, Leeds LS26 8BS

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com

www.rocol.com

Technical Data



Performance you can trust



BELT DRESSING Spray



Conditioning spray for most types of belt drives

Property	Test Method	Result
Appearance	Visual	Colourless, adhesive film
Base Type	N/A	Hydrocarbon Polymer
Propellant	N/A	Carbon dioxide (CO ₂)
Solvent	N/A	Non-chlorinated hydrocarbon
Water Solubility	N/A	Insoluble
Metal Detection:		
Aerosol Cap	Equivalent sphere size	>3.0mm
Actuator	Equivalent sphere size	>3.0mm

Values quoted above are typical and do not constitute a specification.

BELT DRESSING Spray is produced at a Halal Control Certified Site (Swillington UK) and is certified as Halal only where the Halal Control Logo is displayed on the product label (certificate registration number C-912-350-05-01/1).



Metal detectable caps to reduce potential contamination risk.

Safety Data Sheets

Safety data sheets are available for download from our website <u>www.rocol.com</u> or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. Issue: 4 Date: 07-15

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL ROCOL A division of IT W Ltd



