

## 5030 Static Port Protection Tape



Backing:	LDPE Film	
Adhesive:	Acrylic	
Liner:	N/A	
Colors:	Gloss Yellow, Orange, Red (Other Colors Available)	
Size Options:	Incremental widths 1/4" - 54" x 108ft	
	Easy-Tear Version & Master Rolls Available	

## **Applications**

- High visibility masking of critical static ports
- Color coding and part marking
- Temporary holding and sealing

	Temporary	outdoor	curfaco	protoction
•	remporary	outdoor	Sunuce	protection

• Temporary attachment and splicing of masking materials

Features	Benefits
LDPE Film	Conformable for irregular surfaces
	<ul> <li>Withstands temporary outdoor exposure</li> </ul>
	<ul> <li>Excellent moisture barrier properties</li> </ul>
Acrylic Adhesive	<ul> <li>Resistant to citrus-based cleaners</li> </ul>
	<ul> <li>holds up to power washing</li> </ul>
	UV and solvent resistant
	<ul> <li>Firm bond with virtually no edge bleed</li> </ul>
	Will not crack or crease
	Excellent high and low temperature performance
	Low in halogens and leachable chlorides

## **Typical Test Values**

	Standa	rd UOM	Metric U	ЛОМ	Test Method	
Total Thickness	5.5	mils	0.140	mm	PSTC-133	
Substrate Thickness	4.5	mils	0.114	mm	PSTC-133	
Adhesion to Steel	50	oz/in	5.47	N/cm	ASTM D-3330	
Tensile Strength	11	lb/in	19.26	N/cm	ASTM D-3759	
Elongation	400%					
Application Temperature	50 to 120 °F		10 to 49 °C			
Operating Temperature	-40 to 190 °F		-40 to 8	38 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80  $^\circ F$  Standard Shelf Life (at 25  $^\circ C)$ : 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of fitness for a particular purpose), or a representation for which BERRY desumes any legal responsibility.



## 25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com 1/17/19