

ACC 2200

Product Group	Cleaner
Description	ACC 2200 is an alkaline cleaner for aircraft exterior and interior surfaces.
Characteristics	Easy to mix with water Dip application is possible. For use on all aircraft metals and two component coatings. Does not affect aluminum. No crazing of Plexiglas. Nonflammable
Specification	AMS 1526C AMS 1550B
Application	Tanks and associated equipment preferably manufactured of stainless steel. Mix 1 part of ACC 2200 with up to 9 parts of water by volume. Stir well. Apply by non atomizing spray or mop. Agitate surface with soft bristle. For less contaminated surfaces, mix 1 part of ACC 2200 with up to 30 parts of water by volume. Clean with high pressure cold water. Mix 1 part of ACC 2200 with 10-20 parts of water by volume when applied with foam generator. Mix 1 part of ACC 2200 with 50-100 parts of water by volume for interior cleaning. Mix 1 part of ACC 2200 with 3-20 parts of water by volume in a dip tank. Leave parts in the (ultrasonic) tank for 5-15 minutes at a temperature of 65-80°C.
Toxicity and Hazards	Before use always refer to MATERIAL SAFETY DATA SHEET for precautionary, handling and first aid information. Protective clothing, made from alkali resistant materials, must be worn when working with this cleaner. May cause eye and skin irritation. Avoid exposure to high concentrations of vapor. Use with adequate ventilation. Do not swallow. Be careful when opening containers to avoid spurting of contents. Dispose of ACC 2200 mix with dirt residues per applicable regulations. Refer to MATERIAL SAFETY DATA SHEET for additional disposal information.
Storage	Store at a temperature between 5-35°C.
Shelf life/Packing	24 Months/ 25 KG Pail

Notice

The provided information in this document is given in good faith and based on our current knowledge. It is indicative information only and never binding. It must on no account be used as a substitute for necessary preliminary tests that must ensure the suitability of our product.

TDS 2200 - 02/13