

## ACC 2220

Product Group	Cleaner
Description	ACC 2220 is a heavy duty alkaline cleaner for aircraft exterior surfaces.
Characteristics	Easy to mix with water.
	Safe on Plexiglas
	Does not attack metals or well-bonded painted surfaces.
	No hydrogen embrittlement on high strength steels.
	Nonflammable
Specification	MIL-PRF-85570E TYPE II
Application	Tanks and associated equipment preferably manufactured of stainless steel.
	Mix 10 parts of ACC 2220 with 50-90 parts by volume of clean water. Stir well.
	Apply by non atomizing spray or mop.
	Activate surface with soft bristle.
	Mix 10 parts of ACC 2220 with 90-150 parts of water by volume for less contaminated surfaces.
	Keep surface wet with cleaner.
	Clean with high pressure cold water.
	Mix 10 parts of ACC 2220 with 90 parts of water by volume if application by means of foam generator is required.
Toxicity and Hazards	Before use always refer to <b>MATERIAL SAFETY DATA SHEET</b> for precautionary, handling and first aid information.
	Protective clothing, made from alkali resistant materials, must be worn when working with this cleaner.
	May cause eye and skin irritation.
	Avoid exposure to high concentrations of vapor.
	Use with adequate ventilation.
	Do not take orally.
	Dispose of ACC 2220 mix with dirt residues per applicable regulations. Refer to <b>MATERIAL SAFETY DATA SHEET</b> for additional disposal information.
Storage	Store at a temperature between 5-35°C.
Shelf life/Packing	24 Months/ 25 KG Pail

### Notice

The provided information in this document is given in good faith and based on our current knowledge. It is indicative information only and never binding. It must on no account be used as a substitute for necessary preliminary tests that must ensure the suitability of our product.

TDS 2220 - 02/13